

Soldering Station

Features:

- · High quality four-core wire heater
- Smart recognition of working or non-working status.
- Automatic standby, shutdown with smart time setting.
- Temperature locking.
- Beep alarm function available.
- \bullet Temperature read out in ${}^\circ\!\mathbb{C}$ and ${}^\circ\!\mathbb{F}$
- MCU controlled temperature calibration.
- Simulate bar indicating heating up status.
- User-friendly menu enables system setting easier.
- Separate iron stand to save room and to make easier deposit.
- New design with LCD display screen making control visualization.
- Buttons(1,2,3) for pre-setting or switching frequently used temperature.
- Low-voltage heater separated from power supply to keep soldering work safer.
- Soldering tip designed separate from heater and using exchangeable T**900** series to save use-cost.(Page 20)

Package list	Standard Packing:
Main unit: 1Unit	Inner box: 31.5x27x15.2(CM)
Handle set: 1 PCS	N.W.: 2.58KG
Iron stand: 1 PCS	G.W.: 2.81KG
AC cord: 1 PCS	
Manual : 1 copy	
Cleaning sponge: 1 PCS	



Specification: Voltage:

Power:	80W
Heater voltage:	28VAC
Temperature range:	150-480°C/302-896°F
Temperature offset range:	±50°C/±90°F
Temperature stability:	±2°C(in still air, no load)
Automatic stand-by time:	1-120 minutes
Automatic shutdown time:	1-120 minutes
Temperature adjustment:	5 digits (Default)/1 digit (Fine-tuning)
Heater:	High quality four-core wire heater
Tip-to-ground impedance:	<2ΩΩ

<2mV

175(L)*115(w)*95(H) mm

230VAC 50Hz

Other Soldering Irons in the Range ST-60 60W Iron ST-100 100W Iron

Tip-to-ground voltage:

Dimensions:

