





## SM3300 - Series 3300W DC POWER SUPPLIES



One or Three phase input

Models	Voltage range	Current range
SM 18-220	0 - 18 V	0 - 220 A
SM 66-AR-110 Autoranging output	0 - 33 V 0 - 66 V	0 - 110 A 0 - 55 A
SM 100-AR-75 Autoranging output	0 - 50 V 0 - 100 V	0 - 75 A 0 - 37.5 A
SM 330-AR-22 Autoranging output	0 - 165 V 0 - 330 V	0 - 22 A 0 - 11 A
SM660-AR-11 Autoranging output	0 - 330 V 0 - 660 V	0 - 11 A 0 - 5.5 A



### Features

- Designed for long life at full power
- Excellent dynamic response to load changes
- Protected against all overload and short circuit conditions
- EMC surpasses CE requirements: low emission & high immunity
- Low audible noise: fan is temperature controlled
- Available Options : Software control and Interfaces, High Speed Programming, Two-Quadrant Output - PowerSink

### Functionalities

- Operation on single and three phase input voltages
- Standard Ethernet interface
- Large user display, menu driven operations
- Durable digital encoders for voltage and current adjustment
- Plug and play optional interfaces

	SM 18-220	SM 66-AR-110	SM 100-AR-75	SM 330-AR-22	SM 660-AR-11
<b>DC Power terminals</b>					
voltage	0 - 18 V	0 - 66 V	0 - 100 V	0 - 330 V	0-660V
current	0 - 220 A	0 - 110 A	0 - 75 A	0 - 22 A	0-11 A
<b>AC Input</b>					
1 or 3 phase, 48 - 62 Hz	180-528 V	180-528 V	180-528 V	180-528 V	180-528 V
rated voltage range	200 - 480 V	200 - 480 V	200 - 480 V	200 - 480 V	200 - 480 V
rated frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
rated current	Max. 16 A	Max. 16 A	Max. 16 A	Max. 16 A	Max. 16 A
current (400 V / 3 ph, 3300W)	5.8 A	5.6 A	5.6 A	5.6 A	5.6 A
power factor, 3300W, 1750W	0.94, 0.92	0.94, 0.92	0.94, 0.92	0.94, 0.92	0.94, 0.92
<i>Power Derating vs input</i>					
<i>Single phase:</i>					
230 V : P <sub>out</sub> max (W), I <sub>in</sub> (A)	3050, 16	3100, 16	3100, 16	3200, 16	3200, 16
205 V : P <sub>out</sub> max (W), I <sub>in</sub> (A)	2650, 16	2700, 16	2700, 16	2800, 16	2800, 16
180 V : P <sub>out</sub> max (W), I <sub>in</sub> (A)	2300, 16	2400, 16	2400, 16	2400, 16	2400, 16
<i>Three phase</i>					
190 V : P <sub>out</sub> max (W), I <sub>in</sub> (A)	3300, 12.5	3300, 12.5	3300, 12.5	3300, 12.5	3300, 12.5
180 V : P <sub>out</sub> max (W), I <sub>in</sub> (A)	3100, 12.5	3100, 12.5	3100, 12.5	3100, 12.5	3100, 12.5
power factor single phase	0.99	0.99	0.99	0.99	0.99
internal fuses	20 AT	20 AT	20 AT	20 AT	20 AT
standby input power (V <sub>o</sub> =I <sub>o</sub> =0)	30 W	30 W	30 W	30 W	30 W
standby input power (V <sub>o</sub> =V <sub>max</sub> )	60 W	50 W	50 W	50 W	60 W
<b>Efficiency</b>	89 %	90 %	90 %	91 %	92 %
400 V AC, 3 ph input, full load					
<b>Regulation</b>					
Load 0 - 100% <b>CV</b>	2.5 mV	5 mV	5 mV	5 mV	5 mV
Line 180 - 528 V AC <b>CV</b> (external voltage sense)	0.2 mV	1 mV	1 mV	3 mV	4 mV
Load 0 - 100% <b>CC</b>	12 mA	6 mA	2 mA	1.2 mA	1.2 mA
Line 180 - 528 V AC <b>CC</b> (internal voltage sense, after warm up)	3 mA	1 mA	0.5 mA	0.2 mA	0.2 mA
		33 / 66V	50 / 100 V	165 / 330 V	330 / 660 V
<b>Ripple + noise</b>					
rms (BW=300 kHz) <b>CV</b>	3 mV	7 mV	7 mV	10 mV	15 mV
p-p (BW=20 MHz) <b>CV</b>	12 mV	18 mV	22 mV	50 mV	120 mV
rms (BW=300 kHz) <b>CC</b>					
p-p (BW=20 MHz) <b>CC</b>	50 mA	15 / 7.5 mA	6 / 2 mA	4.5 / 1.5 mA	1.8 / 0.6 mA
<i>CC-ripple at full load</i>	250 mA	90 / 45 mA	60 / 20 mA	24 / 8 mA	7.5 / 2.5 mA
<b>Programming &amp; monitoring accuracy</b> (excluding INT MOD ANA)					
Voltage	± 0.1%	± 0.1%	± 0.1%	± 0.1%	± 0.1%
Current	± 0.18%	± 0.25%	± 0.25%	± 0.15%	± 0.15%
<b>Temp. coeff., per °C<sup>-1</sup></b> <b>CV</b>			35.10 <sup>-6</sup>		
<b>CC</b>			60.10 <sup>-6</sup>		
<b>Stability</b> <sup>1</sup> after 1 hr warm-up during 8 hrs <b>CV</b>					
<b>CC</b>			6.10 <sup>-5</sup>		
t <sub>amb</sub> = 25 ± 1 °C, V <sub>in</sub> = 400 VAC (internal voltage sensing for CC-stab.)			9.10 <sup>-5</sup>		

	SM 18-220	SM 66-AR-110	SM 100-AR-75	SM 330-AR-22	SM 660-AR-11
<b>Programming speed</b> <sup>2</sup>					
Standard Version (resistive load)					
<b>Rise time (10 - 90%)</b>					
output voltage step	0 → 15 / 18 V	0 → 33 V	0 → 50V	0 → 165 V	0 → 330 V
time, (load = 3300W)	4 / 5.5 ms	1.6 ms	3.6 ms	3.8 ms	4.2 ms
time, (load = 330 W)	2.2 / 2.6 ms	1 ms	2 ms	2 ms	2.5 ms
output voltage step	-	0 → 66 V	0 → 100 V	0 → 330 V	0 → 660 V
time, (load = 3300W)	-	7 ms	15 ms	15 ms	15 ms
time, (load = 330 W)	-	3.7 ms	8 ms	8 ms	7.5 ms
<b>Fall time (90 - 10%)</b>					
output voltage step	15 / 18 V → 0 V	33 V → 0 V	50 V → 0 V	165 V → 0 V	330 V → 0 V
time, (load = 3300W)	6 / 8 ms	3 ms	6 ms	6 ms	6 ms
time, (load = 330 W)	52 / 75 ms	33 ms	65 ms	65 ms	70 ms
output voltage step	-	66 V → 0 V	100 V → 0 V	330 V → 0 V	660 V → 0 V
time, (load = 3300W)	-	11 ms	26 ms	25 ms	28 ms
time, (load = 330 W)	-	100 ms	260 ms	250 ms	270 ms

Notes: 1. Measured at full load. 2. Signal latency depends on the interface used & data traffic. 3. See "Safety instructions" 4. With optional Interface.

Programming speed <sup>2</sup> High Speed Version (resistive load)	SM 18-220 Option P300	SM 66-AR-110 Option P302	SM 100-AR-75 Option P303	SM 330-AR-22 Option P304	SM 660-AR-11 Option P305
<b>Rise time (10 - 90%)</b>					
output voltage step	0 → 15 / 18 V	0 → 33 V	0 → 50V	0 → 165 V	0 → 330 V
time, (load = 3300W)	0.17 / 0.24 ms	0.34 ms	0.46 ms	0.38 ms	0.8 ms
time, (load = 330 W)	0.13 / 0.15 ms	0.33 ms	0.46 ms	0.35 ms	0.7 ms
output voltage step	-	0 → 66 V	0 → 100 V	0 → 330 V	0 → 660 V
time, (load = 3300W)	-	0.44 ms	0.53 ms	1.6 ms	2.8 ms
time, (load = 330 W)	-	0.35 ms	0.47 ms	0.8 ms	2.0 ms
Ripple @ full load Typical (rms / pp)	15 mV / 50 mV	25 mV / 70 mV	35 mV / 120 mV	50 mV / 120 mV	60 mV / 250 mV
<b>Output Capacitance</b> (typical)	750 $\mu$ F	315 $\mu$ F	95 $\mu$ F	31 $\mu$ F	15 $\mu$ F
<b>Fall time (90 - 10%)</b>					
output voltage step	15 / 18 V → 0 V	33 V → 0 V	50 V → 0 V	165 V → 0 V	330 V → 0 V
time, (load = 3300W)	0.19 / 0.27 ms	0.34 ms	0.42 ms	0.45 ms	0.82 ms
time, (load = 330 W)	0.52 / 0.75 ms	1.6 ms	1.4 ms	4.3 ms	8 ms
output voltage step	-	66 V → 0 V	100 V → 0 V	330 V → 0 V	660 V → 0 V
time, (load = 3300W)	-	0.58 ms	0.53 ms	2.1 ms	3.4 ms
time, (load = 330 W)	-	5.7 ms	5 ms	17 ms	30 ms

	SM 18-220	SM 66-AR-110	SM 100-AR-75	SM 330-AR-22	SM 660-AR-11
<b>Recovery time</b> range		33 V / 66 V	50 V / 100 V	165 V / 330 V	330 V / 660 V
recovery within	50 mV	100 mV	100 mV	500 mV	800 / 500 mV
di/dt of load step	2.7 A/ $\mu$ s	1.7 / 0.7 A/ $\mu$ s	1.1 / 0.5 A/ $\mu$ s	0.35 / 0.17 A/ $\mu$ s	0.16 / 0.08 A/ $\mu$ s
output voltage	15V	30V / 60V	45V / 90V	150 / 300 V	300 / 600 V
time, @ 50 - 100% load step	100 $\mu$ s	100 $\mu$ s	100 $\mu$ s	100 $\mu$ s	100 $\mu$ s
max. deviation	250 mV	260 / 180 mV	180 / 80 mV	1.8 / 1.4 V	2.2 / 1.8 V
<b>Output impedance</b>					
CV, 0-1 kHz	< 0.8 m $\Omega$	< 3 m $\Omega$	< 1.8 m $\Omega$	< 30 m $\Omega$	< 60 m $\Omega$
CV, 1-100 kHz	< 12 m $\Omega$	< 25 m $\Omega$	< 18 m $\Omega$	< 250 m $\Omega$	< 600 m $\Omega$
<b>Pulsating load</b>					
max. tolerable AC component of load current					
f > 1 kHz	25 A <sub>rms</sub>	20 A <sub>rms</sub>	11 A <sub>rms</sub>	<i>t.b.d.</i>	<i>t.b.d.</i>
f < 1 kHz	220 A <sub>peak</sub>	110 A <sub>peak</sub>	75 A <sub>peak</sub>	22 A <sub>peak</sub>	11 A <sub>peak</sub>

<b>Insulation</b>					
AC power terminals / DC power term. creepage / clearance		3750 V <sub>rms</sub> (1min.) 8 mm		3750 V <sub>rms</sub> (1min.) 8 mm	3750 V <sub>rms</sub> (1min.) 8 mm
AC power terminals / case DC power terminals / case		2500 V <sub>rms</sub> 1000 V DC <sup>3</sup>		2500 V <sub>rms</sub> 1330 V DC <sup>3</sup>	2500 V <sub>rms</sub> 1400 V DC <sup>3</sup>
<b>Safety</b>	cTUVus / EN 60950 / EN 61010				
<b>EMC Power Supply Standard</b>	<b>EN 61204-3</b> , Emission: residential, <b>light</b> industrial environment (CISPR22-Class B) Immunity: industrial environment				
<b>Generic Emission Generic Immunity</b>	<b>EN 61000-6-3</b> , residential, <b>light</b> industrial environment (EN 55022 B) <b>EN 61000-6-2</b> , industrial environment				
<b>Operating Temperature at full load</b>	- 20 to + 50 °C derate output to 75% at 60 °C				
<b>Humidity</b>	maximum 95% RH, non condensing, up to 40 °C maximum 75% RH, non condensing, up to 50 °C				
<b>Storage temperature</b>	- 40 to + 85 °C				
<b>Thermal protection</b>	output shuts down in case of insufficient cooling				
<b>MTBF</b>	500 000 hrs				

	SM 18-220	SM 66-AR-110	SM 100-AR-75	SM 330-AR-22	SM 660-AR-11
<b>Hold-Up time</b> (@ 400 VAC input)					
V <sub>out</sub> = 100%, P <sub>out</sub> = 3300 W	6 ms	12 ms	12 ms	12 ms	12 ms
I <sub>out</sub> = 100%, P <sub>out</sub> = 3300 W	13 ms	13 ms	13 ms	13 ms	13 ms
V <sub>out</sub> = 100%, P <sub>out</sub> = 1750 W	18 ms	24 ms	24 ms	24 ms	24 ms
<b>Turn on delay after mains switch on</b>	1.4 s				
Inrush current	15 A				

Notes: 1. Measured at full load. 2. Signal latency depends on the interface used & data traffic.

3. See "Safety instructions"

4. With optional Interface.

	SM 18-220	SM 66-AR-110	SM 100-AR-75	SM 330-AR-22	SM 660-AR-11
<b>Series operation</b> max. total voltage Master / Slave operation <sup>4</sup>	1000 V <sup>3</sup> yes	1000 V <sup>3</sup> yes	1000 V <sup>3</sup> yes	1330 V <sup>3</sup> yes	1400 V <sup>3</sup> yes
<b>Parallel operation</b> Normal Master / Slave operation <sup>4</sup>	no limit maximum 8 units				
<b>Remote sensing</b> max. voltage drop per load lead	2 V				
<b>Limits</b> <b>Voltage</b> adjust range <b>Current</b> adjust range	0 - 101 % 0 - 101 %				
<b>Potentiometers</b> front panel control with knobs resolution	15 bits				
<b>Meters</b> scale voltage scale current accuracy read output read limit setting	4 digit 0.00 - 18.00 V 0.0 - 220.0 A 0.2% + 2 digit 0.3% + 2 digit	4 digit 0.00 - 66.00 V 0.0 - 110.0 A 0.2% + 2 digit 0.3% + 2 digit	4 digit 0.0 - 100.0 V 0.00 - 75.00 A 0.2% + 2 digit 0.3% + 2 digit	4 digit 0.0 - 330.0 V 0.00 - 22.00 A 0.2% + 2 digit 0.3% + 2 digit	4 digit 0.0 - 660.0 V 0.00 - 11.00 A 0.2% + 2 digit 0.3% + 2 digit

<b>Mounting</b>	stacking of units allowed, air flow is from left to right
<b>AC Terminals (CON D)</b>	screw terminals for wire 2.5 - 4 mm <sup>2</sup> , 3 phase + earth (no neutral)
<b>DC Terminals (CON B1 &amp; B2)</b>	M8 bolts
<b>Programming connectors (LAN)</b>	standard with RJ45-connector for Ethernet at rear panel
<b>Interlock (CON A)</b>	input for contact at rear panel
<b>Cooling</b> audio noise level  air flow	low noise blower, fan speed adapts to temperature of internal system ca. 50 dBA at full load, 25 °C ambient temperature, 1 m distance ca. 57 dBA at full load, 50 °C ambient temperature, 1 m distance From left to right
<b>Enclosure</b> degree of protection	IP20
<b>Dimensions</b> front panel: h x w behind front panel: h x w x d	88.1 x 483 mm (19", 2 U) 86 x 448 x 455 mm (excluding feet) with optional interfaces the required depth is 500...530mm
<b>Weight</b>	15 kg

CV = Constant Voltage  
CC = Constant Current

Specifications measured at  
 $t_{amb} = 25 \pm 5 \text{ }^\circ\text{C}$  and  $V_{in} = 400 \text{ VAC}$ ,  
50 Hz unless otherwise noted.

The information in this document is  
subject to change without notice.

Notes:

1. Measured at full load.
2. Signal latency depends on the interface used and data traffic.
3. See safety Instructions in the operating manual.
4. With optional 'plug and play' interface.

### Typical Applications

- Solar inverter testing, PV-Simulation
- Car testing systems
- ATE in industrial production lines
- Plasma chambers
- Automotive battery simulations
- Controlled battery (dis)charging
- Lasers
- Sustainable energy
- Driving PWM-Controlled DC motors
- Accurate current sources
- Aerospace and military equipment

### Standard Features



#### Digital CV- and CC-Settings

Reliable, long-life digital encoders are implemented at the front panel. Includes total front panel lock (also for CV- / CC-knobs) and a coarse or fine pitch adjustment depending on the turning speed.



#### Ethernet Interface

Ethernet interface for programming and monitoring



#### Sequencer

Arbitrary Waveform generator or standalone automation.



#### High Voltage Isolation

A high DC output isolation allows floating operation up to 1000 V for SM18-220, SM66-AR-110 and SM100-AR-75, and up to 1330V and 1400 V for SM330-AR-22 and SM660-AR-11.



#### USB-Input

Not yet available: Front and rear panel USB-Input for exchange of settings and waveforms (Host / Type-A).

### Options



#### Software control and Interfaces

Field installable interfaces:

- Master / Slave controller
- Isolated Contacts
- Serial controller with multiple protocols: RS 232, RS 485, RS 422 and USB (Device)
- Digital I/O
- Isolated Analog Programming
- Simulation interface

Order Codes :

- INT MOD M/S
- INT MOD CON
- INT MOD SER
- INT MOD DIG
- INT MOD ANA
- INT MOD SIM



#### High Speed Programming

A 10 to 20 times higher programming speed (down to 0.2ms rise time at full load) and lower output capacitance. Excellent for laser applications, test systems or as current source with low parallel capacitance as used in plasma chambers.

Order Codes :

- SM 18-220 – P300
- SM 66-AR-110 – P302
- SM 100-AR-75 – P303
- SM 330-AR-22 – P304
- SM 660-AR-11 – P305



#### Two-Quadrant Output Power Sink

Two quadrant operation maintains the DC output voltage constant regardless the output power is positive or negative. Ideal for PWM-speed controlled DC-Motors and ATE systems.

Order Codes :

- SM 18-220 – P306
- SM 66-AR-110 – P308
- SM 100-AR-75 – P309
- SM 330-AR-22 – P310
- SM 660-AR-11 – P311

